



Application

Atlanta Drainmaster Sanitary pipe is designed for above and underground sanitary piping system. It is ideal for Drain, Waste and Vent Installations. Approved by contractors, architects, engineers and private home-owners. Conforms with PNS 1950 / ASTM D2729 specification.





With Built-in Flow Guide



Unique Slope Desigr for Smooth Flow.

For Superior and Leak Proof Jointing:







Specifications

Thickness

OD —		
00 —	T	
	Length	

Outside Diameter (OD)	Nominal Size	Thickness		Length
mm	in	S600 mm	S1000 mm	М
57.15	2	1.9	2.50	3
82.55	3	2.5	3.70	3
107.10	4	2.5	3.80	3



Elbow 45°			
	in		
	2 3 4		

Tee			
0	in		
1-1-	2		
	3		
	4		


Wye			
	in		
	2 3 4		

in

2 3 4



in
2 3 4



Double Wye*	
	in
	2 3 4

Cross Tee*		
	in	
	2 3 4	
NEW DESIGN	4	

Wye Reducer	

	Double Wye Reducer*		
in		in	
3 x 2 4 x 2 4 x 3		3 x 2 4 x 2 4 x 3	

Tee Reducer			
	in		
	3 x 2 4 x 2 4 x 3		

Cross Tee Reducer*			
	in		
	3 x 2 4 x 2 4 x 3		

Bushing Reducer		
	in	
Q	3 x 2 4 x 2 4 x 3	

Coupling Reducer*		
	in	
	4 x 2	
	4 x 3	

Tap Elbow 90°		
	in	
	2 x 1-1/4 2 x 1-1/2	

Tap Tee		
	in	
	2 x 1-1/4 2 x 1-1/2	

Transition Coupling*		
	in	
	2	
	3	
	4	

Atlanta Low VOC PVC Cement		
	in	
ATLANTA UPVO SOLVENT GEMENT	100 cc	
PORAMETANY RACTIFICAL VINITALISM MODIFICALLY NATIONAL VINITALISM AND TO THE RESERVE OF THE STATE	200 cc	
% -8	400 cc	
Name-free I Environment Friedly Social Sory	946 cc	

*FABRICATED



35th Flr. Atlanta Center Bldg., No. 31 Annapolis St. Greenhills, San Juan City **Tel. No.:** 8723-0781 to 88 | Fax No.: 7744-4703 / 8584-2997

Like Us on Facebook: atlantaindustriesincorporated

Subscribe to Our Youtube Channel: Atlanta Industries Inc.

