


Carat Wastewater Underground Tank




Benefits

- ✓ Unrivalled fitting accuracy
- ✓ Ribbed tank base
- ✓ Groundwater-stable thanks to its extremely stable construction
- ✓ Very high stability thanks to modern production methods
- ✓ Made of 100% recycling material
- ✓ Easy to transport, 5 -9 tanks per pallet
- ✓ Up to 36 complete wastewater systems or 45 wastewater tanks per lorry



Flush with ground level


- ✓ Unique fit accuracy of the components
- ✓ Suitable for vehicle loading
- ✓ Numerous seals to effectively stop dirt getting into the tank
- ✓ The height of the telescopic tank dome can be smoothly adjusted
- ✓ The telescopic tank dome can additionally be inclined by 5° to suit the local conditions



Telescopic dome shaft 600 cast iron suitable for vehicles

- ✓ Impact-resistant

Easy and safe assembly



SCAN TO DOWNLOAD BROCHURE



35th Flr. Atlanta Center Bldg., No. 31 Annapolis St. Greenhills, San Juan City
 Tel. No.: 8723-0781 to 88 | Fax No.: 7744-4703 / 8584-2997
 Website: www.atlanta.ph | Email Sales: marketing@atlanta.ph
 Like Us on Facebook: [atlantaindustriesincorporated](https://www.facebook.com/atlantaindustriesincorporated)
 Subscribe to Our Youtube Channel: Atlanta Industries Inc.

Carat S Underground Tank

Choose your tank size



Carat S underground tank Suitable for vehicle loading

Size 2,700 – 6,500 litres. Designed to be used in conjunction with the vehicle loading telescopic tank dome. The access dome is designed in accordance with DIN testing.



Illustration shows 4,800 litre tank with telescopic dome shaft 600 for pedestrian loading



Tank dome Maxi
Order no. 371040



Tank dome Mini
Order no. 371041




Tank dome Micro
Order no. 371009

Dimensions

Volume [l]	Width B [mm]	Length L [mm]	Height H [mm]	Height H _{tot} [mm]	Height of tank dome H _t [mm]	Inner Ø of tank dome [mm]	Weight [kg]	Order no.
2,700 (700 US gal.)	1565 (61.6")	2080 (81.9")	1400 (55.1")	2010 (79.1")	610 (24.0")	650 – 800 (25.6 – 31.5")	120 (265 lbs)	372024
3,750 (1,000 US gal.)	1755 (69.1")	2280 (89.8")	1590 (62.6")	2200 (86.6")	610 (24.0")	650 – 800 (25.6 – 31.5")	150 (331 lbs)	372025
4,800 (1,250 US gal.)	1985 (78.2")	2280 (89.8")	1820 (71.6")	2430 (95.7")	610 (24.0")	650 – 800 (25.6 – 31.5")	185 (408 lbs)	372026
6,500 (1,700 US gal.)	2190 (86.2")	2390 (94.1")	2100 (82.7")	2710 (106.7")	610 (24.0")	650 – 800 (25.6 – 31.5")	220 (485 lbs)	372027

Technical data

Max. earth covering (without groundwater vehicle loading)	1500 mm (59.1")
Max. vehicle weight	12 to (26456 lbs)
Earth covering required for vehicle loading	800 – 1500 mm (31.5 – 59.1")
Groundwater stability	Up to tank equator
Earth covering required for groundwater stability	800 – 1500 mm (31.5 – 59.1")
Connection	DN 110 / DN 160 / DN 200 on top



Tank

Carat S 2,700 – 6,500 litres




Tank cover



Baffles

Baffles – Carat S 2,700 – 6,500 litres



System packs

